



	a Red b Green	HD16/24A. CRT.RG.Vxx	HD16/24B. CRT.RG.Vxx		
--	------------------	----------------------	----------------------	--	--

	a Red b Green			HD16/24A. CRQ.RG.Vxx	HD16/24B. CRQ.RG.Vxx
--	------------------	--	--	----------------------	----------------------

On request only

	a Red b Green			HD16/24A. CRC.RG.Vxx	HD16/24B. CRC.RG.Vxx
--	------------------	--	--	----------------------	----------------------

	a Red b Green c Yellow			HD16/24A. CRC.RGY.024 24 Vdc only	HD16/24B. CRC.RGY.024 24 Vdc only
--	------------------------------	--	--	--------------------------------------	--------------------------------------

Supply voltage +/- 10%	Connections Tabs 2,8 x 0,8						
Current Vac/dc 15-20mA Vxx = 024 Vxx = 048 Vxx = 110 Vxx = 130 Alternative current 15mA Vxx = 240 Vac Test lamp not available Direct current - 220 Vdc 9mA Vxx= dc 220	<table border="1"> <tr> <td>Bicolour</td> <td>Tricolour</td> </tr> <tr> <td></td> <td></td> </tr> <tr> <td>30</td> <td>40</td> </tr> </table>	Bicolour	Tricolour			30	40
Bicolour	Tricolour						
30	40						

Body material: Polycarbonate V0/UL 94 - Colour: Black
Protection degree: IP54
Led not exchangeable

Working temperature: -20 +60°C
Operating life at TA 25°C: > 100.000 h
Led consumption: 20mA