





	a Red b Green	HD22/30A CRT RG Vxx	HD22/30B CRT RG Vxx		
---	------------------	---------------------	---------------------	--	--

	a Red b Green			HD22/30A CRQ RG Vxx	HD22/30B CRQ RG Vxx
--	------------------	--	--	---------------------	---------------------

	a Red b Green c Yellow	HD22/30A CRT RGY Vxx	HD22/30B CRT RGY Vxx		
---	------------------------------	----------------------	----------------------	--	--

	a Red b Green c Yellow			HD22/30A CRQ RGY Vxx	HD22/30B CRQ RGY Vxx
---	------------------------------	--	--	----------------------	----------------------

Supply voltage +/- 10%	Connections Tabs 2,8 x 0,8		
Current Vac/dc 15-20mA Vxx = 024 Vxx = 048 Vxx = 110 Vxx = 130	Bicolour	Tricolour	Bicolour + Test
Alternative current 25,5mA Vxx = 240 Vac			
Direct current 9mA Vxx = dc 220			
Lamp Test on request, where available			

Body material: Polycarbonate V0/UL 94 - Colour: Black
 Protection degree: IP54
 Led not exchangeable

Working temperature: -20 +60°C
 Operating life at TA 25°C: > 100.000 h
 Led consumption: 20mA